RAY-BAR IGU WITH INTEGRAL MINI-BLINDS

GLASS OPTIONS

- TEMPERED
- MIRRORED
- FIRE LITE
- WIRED
- TINTED
- FROSTED
- X-RAY PROTECTIVE
- WIRE LITE
- BULLET RESISTIVE
- POLYCARBONATE
- LOW-E
- REFLECTIVE

• STANDARD :TILT ONLY FUNCTION

OPTIONAL : TILT AND LIFT


CONTROLLER / OPERATION OPTIONS

MAGNETIC OPERATION (STANDARD U.O.N.) KNOB OPERATOR WAND OPERATOR CORD OPERATOR POWER OPERATOR (REMOTE OR SWITCH)

MINI-BLIND COLOR OPTIONS:

STANDARD: White (S102), Silver (S157) and Cream (S149)

SPECIAL ORDER: Beige (S125), Bright Silver (S156), Pale Grey (S155), Pale Yellow (S106) and Pale Blue (S142)




PERFORMANCE OPTIONS

- LOW-E
- SOUND REDUCTION
- INSULATION
- X-RAY RESISTANT
- FIRE RATED (UL)
- BULLET RESISTANT
- IMPACT RESISTANT

FUNCTIONAL OPTIONS

- ELECTRIC SWITCHABLE PRIVACY
- INTEGRAL MINI BLINDS
- IMAGE PROJECTION



plagiarized or utilized in any competitive or detrimental manner against Ray-Bar as protected by law and/or copyrights. "All Rights Reserved"
the architectural design of projects specifying, incorporating and utilizing genuine Ray-Bar products and assemblies. Ray-Bar designs are not to be copied, altered
Terms of Use: Certain designs and concepts are the exclusive proprietary property and work product of Ray-bar Engineering provided in good faith as a courtest

RADIATION		
	JOB NAME:	
FIRE	LOCATION:	
	ROOM NUMBER:	
BALLISTICS	SHEET OF:	

RAY-BAR IGU WITH INTEGRAL MINI BLINDS

RAY-BAR ENGINEERING CORP.

Toll Free: 1(800) 444-XRAY / 1(800) 444-9729

Telephone: (626) 969-1818 24 Hour Fax: 1(800) 333-XRAY /

1(800) 333-9729

website: www.raybar.com

SCALE N.T.S.

INTEGRAL MINI-BLIND RB-IGU